

STACKER DOOR

THERMALLY IMPROVED SUITE - INLINE FRAME



Stacker doors are a natural evolution of the sliding door. Similar in concept, in practice they incorporate another row of sliding panels into a broader product, typically able to span larger distances



Outer frame corners are mitred to enhance the clean aesthetic. All fixings are made from durable stainless steel



The secure lock assembly features anti-lift pins & is key lockable from both sides



All panels roll on two 50kg rated, ball-bearing carriages which run on anodised track inserts

When specified, flyscreens run on their own tracks, which fix neatly to the exterior of the door frame

All glass is installed into dual vinyl sided rebates, ensuring vibration free glazing. Sliding panels are weatherproofed through dual wool-pile seals at the head, jamb, sill & interlocker

STACKER DOOR

THERMALLY IMPROVED SUITE - INLINE FRAME



NOTE: ALL SIZES ARE TYPICAL RATHER THAN DEFINITIVE. FOR PRACTICAL PURPOSES, WHERE DOOR HEIGHT EXCEEDS 2400mm, A SLIDING PANEL WIDTH RESTRICTION OF 1000mm APPLIES. FOR SIZES OUTSIDE OF THESE PLEASE TALK WITH YOUR VALLEY WINDOWS CONSULTANT

Sizing

Door style & opening detail should be considered as viewed externally

Sizes indicated are the overall door size. For Stud openings add 20mm to both height & width

Glazing

Glazing strength to minimum N3 rating as per AS4055 - 2006

Glazing to be grade A safety glass

Certification

Certified performance data is available for this product on request

Specify

Frame colour, configuration, height, width & depth

Optional: handle type & colour, patio bolts, flyscreen, frame infill, frame equaliser, sill flap, glass type